

12

EUROPEAN PATENT APPLICATION

21 Application number: 84116419.7

51 Int. Cl.⁴: G 07 D 1/00

22 Date of filing: 28.12.84

30 Priority: 03.01.84 US 567688

43 Date of publication of application:
21.08.85 Bulletin 85/34

84 Designated Contracting States:
CH DE FR GB IT LI SE

71 Applicant: Atalla Corporation
2363 Bering Drive
San Jose California 95131(US)

72 Inventor: Atalla, Martin M.
18 Montevista
Atherton CA.94025(US)

74 Representative: Liesegang, Roland, Dr.-Ing.
Sckellstrasse 1
D-8000 München 80(DE)

64 Improved currency-dispensing method and apparatus.

67 Method and means of supplying currency includes assembling and packing currency on a transport medium which is secured within a housing and which is incrementally unpacked under security control to dispense the desired amount of currency. Method and means for assembling and packing currency on the transport medium include adhesive regions on the transport medium for attaching currency thereto in substantially coplanar array to facilitate selective unpacking by non-coplanar manipulation of currency and transport medium. Another embodiment utilizes packets of currency that move along with the adhesive transport medium to facilitate self-contained assembly of units of currency on the transport medium. Equal rates of movement of the next unit of currency and the transport medium assure that only the next unit of currency will be transported on the adhesive medium.




Figure 5

Dr.-Ing. Roland Liesegang

Patentanwalt
European Patent Attorney

0151808

Sckellstrasse 1
D-8000 München 80
Telefon (089) 4 48 24 96

Telex 5214382 pal d
Telekopierer (089) 272 04 80, 272 04 81
Telegramme patemus münchen
Postscheck München 394 18-802
Hypobank München 6 400 194 333
Reuscheibank München 2 603 007

ATALLA CORPORATION
San Jose, USA
EU 131 36

1

IMPROVED CURRENCY-DISPENSING METHOD AND APPARATUS

Related Cases

This application is a continuation-in-part application of pending application Serial No. 446,074, entitled "CURRENCY-DISPENSING METHOD AND APPARATUS."

Background of the Invention

Vending machines are commonly used to dispense diverse types and forms of goods, and such machines have even been adapted to dispense packets of cash in predetermined amounts. The popularity of dispensing cash packets seems to be attributable to the simplicity of debiting fixed amounts and to the convenience of using dispensing technology which is similar to the technology used in dispensing such packaged goods as cigarettes and candy bars. Machines of this type are disclosed in the literature (see, for example, U. S. Patents 3,662,343 and 3,845,277). One disadvantage associated with conventional cash-dispensing machines is that the packets of cash remain highly vulnerable to pilferage in the course of manually inserting cash into packets and in the course of loading packets into the dispensing machines.

It is highly desirable to obviate the manual handling of cash (or other forms of money, like traveler's checks, etc.) in the preparation of the cash for dispensing and in the loading of the cash supply into a dispenser. Also, it

is highly desirable to dispense cash (or currency, generally) in arbitrary amounts for greater versatility and accounting possibilities with respect to a recipient's own account balance.

Summary of the Invention

5 In accordance with one embodiment of the present invention, cash or other currency to be dispensed is packaged automatically under secured conditions in continuous array on a transport medium which is assembled
10 within a secure housing to form a currency cartridge which can only be operated under coded control to dispense arbitrary amounts of currency, as desired by users. In another embodiment of the present invention, the units of currency to be dispensed are loaded onto the transport
15 medium internally and incrementally as the currency is being dispensed. This obviates the need for an additional secured workstation external to the dispensing apparatus and also reduces operating costs of the apparatus.

Description of the Drawings

20 Figure 1 is a pictorial view of a currency cartridge showing the operating relationships of the structure;

Figure 2 is a perspective view of a transport medium and attached unit of currency;

25 Figure 3 is a flow chart showing the logical control of the currency cartridge;

Figure 4 is a pictorial view of apparatus for preparing units of currency for dispensing from the transport medium;

30 Figure 5 is a pictorial diagram of a self-contained currency dispenser according to another embodiment of the present invention;

Figure 6 is a plan view of one currency-confining aperture associated with a currency bin; and

35 Figure 7 is a plan view of another currency-confining aperture associated with a currency bin.

Description of the Preferred Embodiment

Referring now to Figure 1, there is shown a pictorial diagram of a currency cartridge 9 installed within a dispensing machine 11. The currency cartridge 9 is contained within a housing 13 which completely surrounds and encloses the reel supply 15 of currency and the operating components, later described herein, to form a secure cartridge that has only an exit port 17 for currency and a connector 19 for control signals. Units of currency 21 which are to be dispensed pass through an exit chute 23 and exit port 17 of the cartridge 13, and through a security port 25 of the machine 11 which is designed using conventional technology to eject dispensed currency and to inhibit unauthorized intrusion by foreign objects.

The reel supply 15 of currency 21 includes a transport medium or web 27 of material such as Mylar or paper, or the like, of high tensile strength which has detector apertures 29 disposed at regular increments along the length of the medium 27. As shown more specifically in Figure 2, the medium 27 (which may be wider or narrower than the currency unit) includes adhesive regions 31 positioned at regular increments along the length of the medium at locations relative to the detector apertures 29 which facilitate attaching each unit of currency 21 to the medium 27 in registration over a corresponding aperture 29. The length of transport medium 27 with units of currency 21 adhesively (but removably) attached thereto is wound onto reel 15 or otherwise packed (as by zig-zag stacking, or the like) for selective unwinding or unpacking of the units of currency, as required to dispense the units 21. The medium 27 is attached to each unit of currency 21, as by conventional gummy, pressure-sensitive adhesive, at a location on each unit that is remote or back from the leading edge 22. Thus, the unit of currency 21 lays substantially in parallel-plane

relationship to the medium 27 (referred to herein as coplanar relationship) and can be "peeled" off the medium 27 by bending the medium 27 away from the unit 21. This bending is accomplished by moving the medium 27 over roller 33. Because of the inherent rigidity of paper currency units 21 (even in used units), the leading edge 22 of a unit 21 "peels" away from medium 27 as it passes over roller 33 and can be gripped by a pair of rollers 35, 37 which exerts a continuing force on the unit 21 in a direction that diverges or strips away from the direction of movement of medium 27. An idler roller 39 may be mounted to pinch the medium 27 against roller 33 and to drive the rollers 35, 37 so that the surface velocities of these moving elements are the same and are controlled by the take-up reel 41 and the drive 43 coupled thereto. A unit of currency 21 which is thus stripped or peeled away from the medium 27 is ejected through the exit chute 23 and exit port 17 of the cartridge and can be transported through a conventional security port 25 of the machine 11 to the recipient. The incremental length of medium 27 moved sufficiently to eject one currency unit 21 is wound onto take-up reel 41.

Of course, more than one supply-reel 15, 15' may be included within the same cartridge 13 where it is desirable to dispense currencies in combinations of different denominations. In that event, one supply reel 15, 15' contains currency units of a different denomination than is contained in other supply reels and each such supply reel of currency units is included within an independently operable system of elements (deleted for clarity) similar to the one system described herein in connection with reels 15, 41, rollers 33, 35, 37, 39, etc. Also, it should be recognized that paper money, scrip, traveler's checks, coins and other tokens of value should be considered in the term currency as used herein.

5 The take-up reel 41 and drive means 43 coupled
thereto are operated incrementally in response to signals
supplied by the cartridge control 44. As illustrated in
the flow chart of Figure 3, operation of the cartridge 13
10 may be in response to an initializing mode or a user-
transaction mode. In the initializing mode 60, a
cartridge 13 newly prepared with units of currency, as
later described in connection with Figure 4, may be
scheduled to be installed in a selected machine 11 which
15 has a known key code (K_1) associated therewith. The
cartridge control 44 may be encoded 62 in conventional
manner to include a security code which renders the
cartridge 13 operable 64 only when installed in machine 11
and properly connected to its control 46 via connectors
19, 45. To establish the proper installation and
20 operation of a cartridge 13, the assembly may be tested 66
under control of cartridge control 44 and machine control
46 to dispense 68 the first unit of "currency" from the
supply reel 15, which first unit may be dummy currency
that is actually a receipt to evidence proper installation
of the cartridge 13 in the selected machine 11.

 In the user transaction mode 70, a user who was
previously identified by the bank or other proprietor of
the currency dispensing machine 11 and who has an account
25 on file can identify himself 72 by his own code word at
the location of machine 11 using conventional interface
means 47 such as credit-card reader, keyboard, etc. The
user's identity may then be verified 74, either off-line
or in interactive connection 76 with the bank, using
30 conventional algorithms, for example, as disclosed in
U. S. Patent 3,938,091 or 4,328,414. Once the identity of
the user is verified, his requested amount of currency 78
may be checked at the bank 80 against the credit balance
standing in his account, and the requisite control code 84
35 may be supplied to the cartridge control 44 to dispense 68

the requested amount of currency.

5 Cartridge control 44 thus is activated to perform several functions. The reel control 18, which locks the supply reel 15 against rotation, is activated to release or drive reel 15 to unwind the transport medium 27 with attached currency. In addition, take-up reel 41 is rotated by drive means 43 to wind up the transport medium 27. This motion of transport medium 27 continues until one or more units of currency sufficient to total the requested amount are "peeled" off the medium and dispensed.

15 To assure a proper accounting for the amount of currency actually dispensed, the pair of gripping rollers 35, 37 may be conductive and normally operated in conductive relationship to each other so that their conductive connection is interrupted as a unit of currency is being rolled through. This detection signal 88 (which can also be generated by optical or other suitable means) is indicative of currency actually dispensed and is used to initiate a debit 90 of the user's account. Of course, similar operation of other supply reels of currency of different denominations can also be controlled by cartridge control 44 in order to dispense a wider variety of amounts of currency consistent with an identified user's outstanding account credits.

25 If a unit of currency 21 is not peeled off the medium 27 after it moves around roller 33, the error detector 92, which may include an optical source and detector, will indicate that the unit is still in position on the medium covering the associated aperture 29. In this event, no unit of currency would have been dispensed (or debited), as expected, and the unit of currency may simply be wound onto the take-up reel 41 as the drive means 43 continues to move the medium 27 an additional distance sufficient to dispense the required unit or units of currency. However,

in accordance with one embodiment of the present invention, this detected error 94 in the operation of the cartridge 13 is applied to alter the cartridge code in a manner which indicates that currency is still contained within the cartridge. When the cartridge is later removed from machine 11 and returned to the bank for disassembly and reloading, this altered code may be detected via connector 19 as an indication that disassembly requires retrieval of currency in take-up reel 41.

Referring now to Figure 4, there is shown a work station at which a supply 100 of currency units is automatically assembled or stacked on the transport medium 27. Adhesive regions 106 are formed at regular intervals along the medium by roller 110 having raised applicator protrusions around its perimeter which pick up adhesive 112 and apply it as a lateral stripe 106 to the medium 27. Conventional, pressure-sensitive, gummy adhesives for this application are commonly available, for example, from 3M Company, Minnesota, and can be applied in continuous operation as disclosed. This adhesive adequately holds a unit of currency in gummy fixation upon the medium for easy "peeling" therefrom without damage to the currency.

A light source and detector 102 at the entrance side of the work station aligns with the apertures 29 and activates the drive means 104 to press the medium 27 with adhesive regions 106 onto the top unit of currency in the supply 100, as illustrated at 113. By this action, the top unit adheres to the medium 27 in position over the associated aperture 29 and with the leading edge (relative to the illustrated direction of movement of the medium 27) well in advance of the adhesive region 106. The units of currency are thus stacked on the medium 27 substantially in parallel-plane relationship 114 to the medium 27. The leading edge or forward boundary of each unit of currency is thus free to "peel" away from the medium 27 when the

medium 27 is moved over roller 33, as previously described. The last unit of "currency" 116 attached to the medium 27 may be dummy currency or a receipt for test operation of the cartridge 13, as previously described.

5 Light source and detector 118 may be located on the outlet side of the work station in alignment with the apertures 29 to provide error signal to the drive means 104 for suitably altering its operation in response to detection of an aperture 29 not covered by an adhered unit of
10 currency.

Referring now to the pictorial diagram of Figure 5, there is shown a section of a currency canister 120 having a plural number of currency bins 122 disposed around the periphery of the canister. The currency canister 120 is
15 mounted to rotate about the central axis 124 in response to the transport medium 27 moving along a path that contacts the perimeter of the canister 120. The surface velocity of the canister 120 is thus the same as the velocity of the transport medium 27 as the medium 27 is
20 moved incrementally from supply reel 126 to take-up reel 128 under control of the motor drive 43. The path taken by the transport medium 27 between supply reel 126 and take-up reel 128 may alternatively pass over the top of the canister 120 (not shown) or pass in a continuous loop
25 between supply and take-up reels 126, 128 (which serve as idler rollers) provided, however, that in each such embodiment the transport medium passes along and in contact with the periphery of the canister 120 with regions of adhesive carried by the transport medium 27, as
30 previously described, disposed on the side thereof facing the periphery of the canister 120.

One or more currency bins 122 may be disposed about the periphery of the canister 120 to position one unit of currency from each bin 122 in a succession along the
35 transport medium 27 at selected, spaced intervals.

Regions of adhesive material 31, as previously described, are positioned along the transport medium to contact the outermost unit of currency in each bin 122 as the transport medium 27 and periphery of the canister 120 move together at the same surface velocity under control of the motor drive 43. A pressure roller 133 may be mounted on the opposite side of the transport medium 27 near the location along the path thereof where the periphery of the canister 120 and the transport medium 27 move along divergent paths. This roller 133 is resiliently biased to press the transport medium 27 and the adhesive material 31 carried thereby firmly against the outermost unit of currency in a bin 122 to assure that such outermost unit of currency adheres to the transport medium 27. Then, as the periphery of the canister 120 and the transport medium 27 progress along divergent paths, the adhered unit of currency 131 is extracted from the bin 122 and carried toward the rollers 33, 35 and 37 to be dispensed in the manner previously described.

Referring additionally to Figures 6 and 7 there are shown plan views of two embodiments of currency-confining apertures associated with the currency bins 122 in the canister 120. In each embodiment, the bin includes a resiliently-biased platform 135 to urge the units of currency outwardly toward the surface as each outermost unit is extracted from the bin. In order to confine the stack of currency within the bin 122, the apertures shown in Figures 6 and 7 each include restrictors that reduce the cross section of the bin at the periphery of the canister 120. These restrictors thus impede the free-flow of currency out of the bin 122 as the canister 120 rotates about its axis 124. In Figure 6, the restrictors include tabs 137 mounted at the sides of the bin 122 to extend inwardly sufficiently to overlay a portion of the width of a unit of currency. In Figure 7, the restrictors include

a pair of rollers 139 mounted across the ends of the bin transverse to the path of movement of the transport medium 27 also to overlay a portion of the length of a unit of currency.

5 In operation, the outermost unit of currency in a currency bin 122 contacts the adhesive material 31 carried by the transport medium 27 at the location 141 where the paths of the medium 27 and the periphery of the canister 120 converge. The periphery of the canister 120, the
10 transport medium 27 and the adhered unit of currency all travel along substantially the same path at the same surface velocity past the pressure roller 133 which enhances the adhesion of the unit of currency to the medium 27. Thereafter, the paths of the periphery of
15 canister 120 and the medium diverge, and the adhered unit of currency 131 is extracted from the bin 122 by "peeling" the unit past the restrictors at the surface of the bin. As the movement continues, the extracted unit of currency 131 advances toward the dispensing rollers 33, 35 and 37,
20 and the canister 120 rotates to position a successive bin 122 into position for extraction therefrom of the next unit of currency to be dispensed.

 Equal numbers of units of currency may be loaded into the bins 122 in the canister 120, and the total number of
25 such units may be entered into a memory register (not shown) in the machine controller 46'. The motor drive 43 may be operated incrementally through a number of currency-dispensing operations, under detection and control of the cartridge control in a manner similar to
30 the operations previously described, until the number of dispensing operations equals the number entered in the memory register of controller 46'. Also, any units of currency not properly dispensed and still adhering to the transport medium 27 in take-up reel 128, as detected by
35 cartridge control 44 in the manner previously described,

can provide indication of the number of units of currency to be retrieved from the take-up reel 128 before it is discarded.

5 It should be understood that the present invention includes other embodiments in which the unit of currency to be dispensed travels along a path substantially in contact with, and at the same velocity as, the transport medium. For example, a canister having a single currency bin 122 may be used where the canister is mounted only to
10 shuttle angularly or translationally between an initial position and a terminal position with the outermost unit of currency in the bin in contact with, and moving at the same velocity as, the transport medium between such two positions. In such embodiments, the pressure roller 133
15 may be an active "pinch" roller that establishes contact between the transport medium and a unit of currency during shuttling of the canister between such two positions to assure adherence of the unit of currency to the transport medium. Thereafter, the transport medium need not be
20 retained in contact with currency in the bin as the canister returns to its initial position for subsequent shuttle movement, as previously described.

Therefore, the currency dispenser and method of the present invention provide units of currency to users at
25 remote locations under conditions that insure high degrees of security upon installation and operation. In addition, currency-dispensing cartridges according to the present invention may directly supply units of currency in different selected denominations for greater versatility
30 compared with conventional prepackaged packets of currency. Also, the improved dispensing scheme with internal self-loading permits a stack of currency to be dispensed a unit at a time without the need for preloading at a remote station.

0151808

Claims

1. Currency-dispensing apparatus c h a r a c t e r i z e d
by:
a transport medium (27);
a supply of currency (21) removably attached to said
5 transport medium in substantially coplanar relationship
therewith;
a work station (33) for altering the coplanar relation-
ship of the transport medium and currency attached there-
to for separating the currency from said transport me-
10 dium; and
drive control means (18;44) for selectively advancing
the transport medium (27) through the work station (33)
for selectively separating the currency from the trans-
port medium.
15
2. Currency-dispensing apparatus as in claim 1, c h a -
r a c t e r i z e d by housing means (13) completely
enclosing the supply of currency and the drive control
means and having an outlet port (17) therein through
20 which currency (21) may be ejected and having connector
means (19) thereon for applying control signals to ope-
rate the drive control means (18;44).
3. Currency-dispensing apparatus as in claim 1 or 2,
25 c h a r a c t e r i z e d by detector means (92) posi-
tioned relative to the work station (33) and responsive
to the passage of currency therethrough for producing
a detector signal indicative of the separation of
currency from the transport medium (27).
30
4. Currency-dispensing apparatus as in one of claims 1
to 3, c h a r a c t e r i z e d by :
reel means (15) containing the transport medium (27)
with attached currency (21) wound thereon;
35 means supporting the reel means (15) for rotational
motion thereof to permit unwinding therefrom of the
transport medium (27) with attached currency (21); and

0151808

lock means interactively associated with the reel means and coupled to the drive control means for retaining the reel means against rotation and for releasing the reel means to selectively unwind the transport medium with attached currency under control of said drive control means.

- 5
10
15
5. Currency-dispensing apparatus as in claim 3, characterized in that said detector means includes a conductive platen and a conductive roller disposed in conductive contact with said platen, said conductive platen and roller being positioned relative to said work station to receive currency separated from the transport medium to produce in response thereto said detector signal which is indicative of currency being separated from the transport medium.
- 20
25
6. Currency-dispensing apparatus as in one of claims 1 to 5, characterized by take-up means (41) positioned relative to the work station for accepting the transport medium (27) which passed therethrough; and sensing means (118) positioned relative to the work station and take-up means along the path of the transport medium for producing a sense signal in response to currency (116) remaining attached to the transport medium past said work station.
- 30
35
7. Currency-dispensing apparatus as in one of claims 1 to 6 characterized by a plural number of supplies (15,15') of currency within the housing means (13), each supply of currency being of different denomination on an individual transport medium (27) and having an individual work station (33) and outlet port (17) and drive control means (18,44) associated therewith.
8. Currency-dispensing apparatus as in one of claims 1 to 7, characterized by security port means (25) disposed contiguous said outlet port (17) for deli-

vering separated currency (21) outwardly and for inhibiting unauthorized entry of objects inwardly.

- 5 9. Currency-dispensing apparatus as claimed in one of claims 1 to 8, characterized in that the length of transport medium (27) has isolated adhesive regions (31) therealong and has individual units of the currency (21) to be dispensed attached thereto at said adhesive regions with at least one edge of each
- 10 unit of currency to be dispensed unattached to the transport medium.
10. Currency-dispensing apparatus as in claim 4 and 9, characterized in that said units of currency
- 15 (21) to be dispensed are attached to said transport medium at said adhesive regions (31) with said edge of each unit being the leading boundary edge thereof for motion of the transport medium in the direction of unwind from said eel means.
- 20 11. Apparatus to prepare units of currency for selective dispensing, characterized by:
- 25 supply means of a length of transport medium (27) having isolated adhesive regions (106) disposed therealong; take-up means for the length of transport medium; a work station disposed intermediate the supply means and the take-up means along a path of movement of the transport medium therebetween, said work station including a supply (100) of units of the currency (116) to
- 30 be dispensed disposed on the side of the transport medium adjacent to adhesive regions (106) therealong, and including on the opposite side of the transport medium platen means for intermittently applying pressure to the transport medium at selected locations therealong
- 35 to contact an adhesive region (106) with a unit of currency (116) at a location thereon which is interior of at least one boundary edge thereof; and

means for moving the transport medium (27) along the path thereof from the supply means through the work station to the take-up means for attaching a plural number of units of currency (116) to be dispensed at intervals along the length of the transport medium.

12. Apparatus as in claim 11, characterized in that said supply means includes means (110, 112) disposed intermediate the supply means and the work station along the path of movement of the transport medium therebetween for applying adhesive to isolated regions (106) on one surface of the transport medium (27).

13. Apparatus as in claim 11 or 12, comprising detector means (102) mounted intermediate the work station and the take-up means along the path of the transport medium (27) therebetween for producing a signal indicative of the attachment of a unit of currency (116) to the transport medium (27).

14. Method of manipulating units of currency to be dispensed selectively, from a transport medium, characterized by: removably attaching units of currency at successive locations along the length of the transport medium in substantially coplanar relationship therewith; and packing the transport medium with attached units of currency for selective unpacking thereof to sequentially remove units of currency from the successive locations between initial and terminal locations along the length of the transport medium.

15. Method as in claim 14, characterized by the step of removably attaching units of currency includes adhesively attaching the transport medium to a unit of currency at a location thereon which is interior of at least one boundary edge thereof.

g

0151808

16. Method as in claim 15, characterized by the step of removably attaching at least one unit of dummy currency at a location near an extreme of the length of transport medium which is unpacked initially.
- 5
17. Method as in one of claims 14 to 16, characterized by the steps of :
- selectively unpacking the transport medium to expose the attached units of currency in sequence;
- 10 disrupting the coplanar relationship of the transport medium and the exposed unit of currency for separating said boundary edge thereof from the transport medium; and
- exerting forces in divergent directions on the transport medium and unit of currency to remove said unit
- 15 from the transport medium.
18. Method as in claim 17, characterized in that said step of selectively unpacking includes moving
- 20 said transport medium in response to an applied control signal and including the step of producing a sense signal in response to removal of the unit of currency from the transport medium.
- 25 19. Method as in claim 18 for dispensing currency as a transaction chargeable to the account of a user, characterized by the steps of:
- supplying control signals to selectively unpack the transport medium in response at least to verification
- 30 of the user and to evaluation of his account; and charging the account of the user in response to a sense signal produced upon removal of a unit of currency from the transport medium.
- 35 20. Method as in claim 10, to dispense currency from a selected machine having a control code associated there-

- with, c h a r a c t e r i z e d by the steps of
assigning code information to the pack of the transport
medium with attached units of currency;
installing the pack in the selected machine; and
5 selectively unpacking the transport medium to separate
at least the one unit of dummy currency in response
to the logical combination of the control code of the
machine and the code information of the pack.
- 10 21. Apparatus as in claim 1 for selectively dispensing
units of currency, c h a r a c t e r i z e d by:
housing means (120,122) for confining a quantity of
units of currency to be dispensed in a configuration
from which single units of currency are extractable
15 in succession;
means (124) supporting said housing means for movement
of the units of currency (131) confined thereby between
first and second positions;
transport means (27) having isolated adhesive regions
20 (31) disposed along the length thereof and being
supported for movement selectively along a path that
passes adjacent the quantity of units of currency (131)
between said first and second positions; and
means (126,128) operable with said housing means (120,
25 122) to engage selected ones of said adhesive regions
(31) and a single unit of currency (131) of said quanti-
ty thereof, and to move said single unit and said trans-
port means substantially along said path at the same
velocities between said first and second positions
30 to adhesively attach said single unit and said trans-
port means.
- 35 22. Apparatus as in claim 21, c h a r a c t e r i z e d
in that said housing means (120,122) is mounted for
angular movement about an axis and includes a selected
number of currency bins (122) disposed substantially
radially outwardly from said axis to confine therein

a stack of units of currency to be dispensed; and said transport means (27) is supported for surface engagement with the outermost unit of currency (131) in a currency bin(122).

5

23. Apparatus as in claim 22, c h a r a c t e r i z e d in that said housing means (120,122) includes a substantially cylindrical canister (120) mounted for rotation about an axis and having a plural number of
10 currency bins (122) substantially radially oriented within the periphery thereof to contain a stack of currency (131) therein with the outermost unit thereof located substantially at the periphery of the canister (120); and

15 said transport means includes a length of web material (27) supported substantially to engage the periphery of the canister at least over an angular portion thereof in which the outermost unit of currency in a currency bin (122) is located.

20

24. Apparatus as in claim 22 or 23, c h a r a c t e r i z e d by restrictor means (137;139) disposed in each of the currency bins near the outer limit thereof to overlay a portion of currency disposed within
25 the bin to inhibit free outward movement therefrom.

25

25. Method of selectively dispensing units of currency from a stacked supply of such currency, c h a r a c t e r i z e d by the steps of:

30

moving the stacked supply of currency to transport the outermost unit of currency along a path between first and second locations;

35

simultaneously moving a transport medium along said path between the first and second locations at substantially the same velocity and in surface contact with said outermost unit;

adherently attaching the outermost unit of currency to the transport medium during the movement thereof between the first and second locations; and

separating the outermost unit of currency from the stacked supply in response to continued movement of the transport medium and attached unit along divergent paths beyond the second location.

5

26. Method according to claim 25, characterized in that in the step of moving, the outermost unit is transported in substantially angular rotation about an axis between the first and second locations.

10

27. Method according to claim 25 or 26, characterized by the step of:
yieldably inhibiting the separation of the outermost unit of currency from the stacked supply to establish separation only in response to said continued movement with the outermost unit adherently attached to the transport medium.

15

1/5

0151808




Figure 1




Figure 2

2/5

0151808




Figure 3




Figure 4




Figure 5




Figure 6




Figure 7